



For more
Information



Please Scan
the QR code

BHARAT BIKER ROYAL 15W50 (SST)

Bharat Biker Royal 15W50 Semisynthetic Technology oil is blend of mineral and synthetic base stock and high-performance additives specially designed keeping in view the high temperature operating conditions encountered in air cooled 4 strokes 2-wheeler engines unlike in the case of passenger car engines, which are water cooled. Further these oils possess special frictional properties required for smooth operation of wet clutches used in these vehicles. These oils provide outstanding oxidation and wear protection for extended oil & engine life.



Application:

- Latest generation high performance Motorcycles and Scooters.
- Suitable for earlier models of Motorcycles, Scooter.

Performance Benefits:

It provides enhanced protection against oxidation and, wear, thereby ensuring smoother performance, cleaner engine and longer engine & oil life.

- Excellent wear protection for engine components.
- Enhanced fuel economy for cost-effective rides.
- Extended drain intervals, reducing maintenance frequency.
- Reduced clutch slippage for smoother operation.
- Utilizes Advanced Active Bond Technology for superior performance and durability.

Typical Data Specifications:

SR. NO.	CHARACTERISTICS	TEST	UNIT	RANGE
1	SAE Rating	-	-	15W50
2	Performance Level	-	-	API SN
3	Appearance	VISUAL	-	C & B
4	Kinematic Viscosity @ 40°C cSt	ASTM D445	mm ² /s	156.8
5	Kinematic Viscosity @ 100°C cSt	ASTM D445	mm ² /s	17.85
6	Viscosity Index min.	ASTM D2270	none	146
7	Flash Point COC °C	ASTM D92	°C	248°C
8	Pour Point °C max.	ASTM D97	°C	-27°C
9	TBN min.	ASTM D2896	mgKOH/g	9.8

***The specifications are subject to variations/development/customization.**

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Available Packing Sizes: 1.2 ltr, 2.5ltrs, 50 ltrs, 55 ltrs, 210 ltrs.

Health & Safety: based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.