



For more
Information



Please Scan
the QR code

BHARAT FULLY SYNTHETIC 0w40 (FST)

Bharat Fully Synthetic MGEO 0w40 (FST) is a high-performance engine oil crafted to offer both fuel efficiency and superior engine protection. Versatile in its application, it is suitable for a diverse range of vehicles, spanning from eco-cars to larger engine models. Compatible with both gasoline and diesel engines, Bharat Fully Synthetic MGEO 0w40 (FST) SN instils confidence by enabling you to demand peak engine performance from today's cutting -edge, highly engineered engines. Its formulation caters to engines operating with tighter tolerances, necessitating the use of lower viscosity oils for optimal function.



Application:

Bharat Fully Synthetic MGEO 0w40 (FST) is SN is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A5/B5, A1/B1, API SN/CF, ILSAC GF-5 or earlier specification 0W-40 lubricant.

Performance Benefits:

It provides enhanced protection against oxidation and, wear, thereby ensuring smoother performance, cleaner engine and longer engine & oil life.

- Excellent performance in low and high temperatures
- Superior high-temperature oxidation stability for long-term engine protection
- Maximizes both short and long-term engine performance
- Independently qualified to improve engine efficiency
- Unsurpassed protection across various driving conditions and temperatures
- Reduces engine deposits for enhanced engine response

Typical Data Specifications:

SR. NO.	CHARACTERISTICS	TEST	UNIT	RANGE
1	SAE Rating	-	-	0w40
2	Performance Level	-	-	API SN
3	Appearance	VISUAL	-	C & B
4	Kinematic Viscosity @ 40°C cSt	ASTM D445	mm ² /s	85
5	Kinematic Viscosity @ 100°C cSt	ASTM D445	mm ² /s	15
6	Viscosity Index min.	ASTM D2270	none	169
7	Flash Point COC °C	ASTM D92	°C	208°C
8	Pour Point °C max.	ASTM D97	°C	-42°C

***The specifications are subject to variations/development/customization.**

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Available Packing Sizes: 1 ltr, 3 ltr, 3.5 ltr, 4.5ltrs, 5 ltr, 10 ltrs, 20 ltr, 26 ltr, 50 ltr, 55 ltrs, 210 ltrs.

Health & Safety: based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.