



For more
Information



Please Scan
the QR code

BHARAT CALSOPLEX PREMIUM CHASSIS GREASE (DARK-GREEN)

BHARAT CALSOPLEX PREMIUM CHASSIS GREASE is a top-tier calcium-based automotive grease made from superior-quality base stocks and carefully chosen additives. With moderately high drop points, resistance to oxidation, and strong thermal and structural stability, this grease ensures reliable performance. Additionally, Bharat Calsoplex Premium Chassis Grease delivers excellent protection against rust and corrosion.



Application:

BHARAT CALSOPLEX PREMIUM CHASSIS GREASE is the perfect choice for lubricating the chassis of various automotive vehicles, including passenger and commercial vehicles, as well as tractors and heavy-duty earthmoving equipment.

Performance Benefits:

- Exhibit excellent film forming characteristics and are therefore also effective as protective greases for chassis and other applications.
- Are recommended for chassis lubrication of automobiles including commercial vehicles, tractors and other heavy-duty equipment.

Recommendation:

Cars | Vans | Motorcycles, Scooters, Mopeds, Quads (ATV) | Trucks and Buses | Agricultural Tractors | RMC Plants | Industrial Machines

Precaution:

It is not recommended for high temperature applications.

Typical Data Specifications:

SR. NO.	CHARACTERISTICS	TEST	UNIT	RANGE
1	Soap Type	-	-	Calcium Soap
2	NLGI Grade	-	-	2.5
3	Colour	VISUAL	-	Dark Green
4	Texture	-	-	Short fibre, Smooth & Buttery
5	Penetration at 25 °C Worked, 60 Strokes	ASTM D.217	mm1	250-290
6	Water Washout at 80 °C, %	ASTM D.1264	-	Less than 3
7	Dropping Point, °C	ASTM D.2265	°C	90-100°C
8	Operating Temperature, °C	ASTM D.2265	°C	50°C

***The specifications are subject to variations/development/customization.**

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Available Packing Sizes: 100 GM, 200 GM, 250 GM, 500 GM, 1 KG, 2 KG, 3 KG, 5 KG, 7 KG, 10 KG, 18 KG, 50 KG, 100 KG, 180 KG.

Health & Safety: based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.