



For more
Information



Please Scan
the QR code

BHARAT RAIL ROAD / APLR / CRUSHER GREASE

BHARAT RAIL ROAD / APLR / CRUSHER GREASE is heavy-duty smooth grey/brown grease based on a lithium complex thickener, high quality paraffinic base stocks combined with the inclusion of extreme pressure additives, and effective rust, oxidation and corrosion inhibitors.

Brilliant APLR GREASE has an operating temperature range from 20 °C to 175 °C .

Application:

BHARAT RAIL ROAD / APLR / CRUSHER GREASE is a prime recommendation for bucket pins and bushes, ball joints, pivot pins, splined shafts, roller bearings, plain bearings and most other heavy-duty applications in mining, cement plants, rock quarries, sugar milling, earthmoving and construction equipment and heavy industry in general.



Performance Benefits:

- Exceptional water resistance
- High oxidation stability
- Maximum structural stability
- Outstanding anti-rust and anti-corrosion properties
- Excellent lubrication under high pressure and temperature
- Exceptional load-bearing capability
- Comprehensive protection for anti-friction bearings

Recommendation:

Cars | Vans | Motorcycles, Scooters, Mopeds, Quads (ATV) | Trucks and Buses | Agricultural Tractors | RMC Plants | Industrial Machines

Precaution:

It is not recommended for high temperature applications.

Typical Data Specifications:

SR. NO.	CHARACTERISTICS	TEST	UNIT	RANGE
1	Soap Type	-	-	Lithium
2	NLGI Grade	-	-	3
3	Colour	VISUAL	-	Brown Green
4	Texture	-	-	Short fibre, Smooth & Buttery
5	Penetration at 25 °C Worked, 60 Strokes	ASTM D.217	mm1	265-295
6	Water Washout at 80 °C, %	ASTM D.1264	-	Less than 3
7	Dropping Point, °C	ASTM D.2265	°C	180-195°C

***The specifications are subject to variations/development/customization.**

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Available Packing Sizes: 100 GM, 200 GM, 250 GM, 500 GM, 1 KG, 2 KG, 3 KG, 5 KG, 7 KG, 10 KG, 18 KG, 50 KG, 100 KG, 180 KG.

Health & Safety: based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.