





Please Scan the QR code

# **BHARAT WB GREASE**

Bharat WB CUP Grease is a premium NLGI 3 grade lithium grease, derived from mineral oil. Specifically designed for general-purpose automotive applications under moderate temperatures and loads, it offers enhanced protection against rusting and water washout.

# **Application:**

Bharat WB CUP is recommended for application in the wheel bearings of various vehicles, including passenger cars, trucks, buses, farm equipment, as well as both on-highway and off-highway commercial vehicles and machinery.



### **Performance Benefits:**

- Offers excellent shear stability enabling long service life and relubrication periods.
- High base oil viscosity enhances lubricant film strength in heavy duty applications protecting components from wear.
- NLGI 3 consistency provides greater resistance to the effects of severe vibration that can be more prevalent in the target applications.
- Polymer technology enhances adhesive properties.

#### **Recommendation:**

Cars | Vans | Motorcycles, Scooters, Mopeds, Quads (ATV) | Trucks and Buses | Agricultural Tractors | RMC Plants | Industrial Machines

#### **Precaution:**

It is not recommended for high temperature applications.

## **Typical Data Specifications:**

SR. NO.	CHARACTERISTICS	TEST	UNIT	RANGE
1	Soap Type	-	-	Sodium
2	NLGI Grade	-	-	3
3	Colour	VISUAL	-	Black Green
4	Texture	-	-	Short fibre, Smooth &
				Buttery
5	Penetration at 25 °C Worked,	ASTM D.217	mm1	240-270
	60 Strokes			
6	Water Washout at 80 °C, %	ASTM D.1264	-	Less than 3
7	Dropping Point, °C	ASTM D.2265	°C	160-170°C

<sup>\*</sup>The specifications are subject to variations/development/customization.

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

**Available Packing Sizes:** 100 GM, 200 GM, 250 GM, 500 GM, 1 KG, 2 KG, 3 KG, 5 KG, 7 KG, 10 KG, 18 KG, 50 KG, 100 KG, 180 KG.

**Health & Safety:** based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.

Since 1984