



For more
Information



Please Scan
the QR code

BHARAT C.OIL (ADVANCE TECHNOLOGIES)

Bharat C.Oil (AT) is a high-performance lubricant specially designed for three-wheelers. This oil provides excellent protection and efficiency in urban and heavy-duty conditions, ensuring optimal engine and transmission performance. It offers superior lubrication, reducing wear and tear on critical components. The advanced formulation enhances fuel economy, minimizes deposits, and provides outstanding resistance to oxidation and thermal breakdown. Bharat C Oil ensures smooth engine operation even under extreme temperature variations, improving overall vehicle reliability and longevity.



Application:

- Specifically formulated for three-wheelers, providing superior lubrication for smooth operation.
- Suitable for engines and transmission systems requiring high-performance lubrication.
- Ideal for stop-and-go city traffic and extended operational efficiency.

Performance Benefits:

- **Enhanced Wear Protection:** Reduces friction and wear, extending the lifespan of engine and transmission components.
- **High Thermal Stability:** Prevents deposits and oil thickening, ensuring consistent performance under varying temperatures.
- **Improved Fuel Efficiency:** Optimized formulation helps in reducing fuel consumption.
- **Smooth Gear Shifting:** Ensures seamless gear transitions for improved ride comfort.
- **Corrosion Resistance:** Protects against rust and corrosion, enhancing component durability.

Recommendation:

Bharat C.Oil is recommended for three-wheelers requiring high-performance gear oil. It ensures smooth transmission and extended component life, making it ideal for commercial and passenger three-wheeler applications.

Typical Data Specifications:

SR. NO.	CHARACTERISTICS	TEST METHOD	UNIT	VALUE
1	SAE Rating	-	-	EP 140
2	Viscosity @ 40°C	ASTM D445	cSt	187
3	Viscosity @ 100°C	ASTM D445	cSt	16.9
4	Viscosity Index	ASTM D2270	-	96
5	Flash Point (COC)	ASTM D92	°C	282
6	Pour Point	ASTM D97	°C	-6
7	Performance Level	-	-	API GL-4

***The specifications are subject to variations/development/customization.**

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

Available Packing Sizes: 500 ML, 1 LTR, 3 LTRS.

Health & Safety: based on available information, this product is not expected to produce any adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the internet. This product should not be used for purposes other than its intended use, if disposing of used product, take care to protect the environment.